



# Kelston® | K-32808-RA

Toilet tank, 1.28 gpf

## Features

- 1.28 gpf (4.8 lpf)
- Right-hand Polished Chrome trip lever
- Coordinates with other products in the Kelston collection
- Combines with the K-32809 bowl to create a complete K-32810-RA toilet
- AquaPiston® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush
- Easy-to-flush canister design requires less force to actuate than a 3" (76 mm) flapper, and has 90% less exposed seal material which resists conditions that cause wear, tear, shrinkage and swelling



## Sustainability



## Available Colors/Finishes

*Color tiles intended for reference only.*

■ 0 White



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.

10-09-2026 01:27 - US-CA

THE BOLD LOOK  
OF **KOHLER**

## Codes/Standards

*Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.*

ASME A112.19.2/CSA B45.1

---

## Technical Information

Flush Type: AquaPiston

Flush Rate: 1.28 gpf (4.8 lpf)

---

## Warranty

*See website for detailed warranty information.*

KOHLER® Toilets and Seats Limited Warranty



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.

10-09-2026 01:27 - US-CA

No image available.

This product is a component and not intended to be a standalone installation.

## Installation

- Supply line sold separately
- 

## Installation Notes

*Install this product according to the installation instructions.*

Product dimensions are nominal and may vary per ASME  
A112.19.2 tolerances.

