

Elate® | K-34909

Pull-out kitchen sink faucet with two-function sprayhead

Features

- Two-function pull-out sprayhead with touch control allows you to switch from aerated stream to ring spray
- Powerful ring spray provides a targeted spray of water to remove stuck-on food
- Compact L-shaped spout and 360° spout rotation offer superior clearance for filling pots and cleaning
- Single lever handle makes adjusting water temperature easy with one hand
- Temperature memory allows faucet to be turned on and off at the temperature set during prior usage
- ProMotion® technology's light, quiet braided hose and swiveling ball joint make the pull-down sprayhead easier and more comfortable to use
- MasterClean™ sprayface features an easy-to-clean surface that withstands mineral buildup and maximizes spray performance
- 1.5 gpm (5.7 lpm) maximum flow rate at 60 psi (4.14 bar)
- KOHLER® ceramic disc valves exceed industry longevity standards for a lifetime of durable performance



Available Colors/Finishes

Color tiles intended for reference only.

- CP Polished Chrome
- VS Vibrant Stainless
- BL Matte Black
- 2MB Vibrant Brushed Moderne Brass



Codes/Standards

ADA, CSA B651 compliant when installed to the specific requirements of these regulations.

ADA CSA B651

ASME A112.18.1/CSA B125.1

NSF/ANSI/CAN 372

NSF/ANSI/CAN 61

DOE - Energy Policy Act 1992

California Energy Commission (CEC)

NSF/ANSI/CAN 61|NSF/ANSI/CAN 372

ADA

ICC/ANSI A117.1

CSA B651

Technical Information

All product dimensions are nominal.

Handle

Handle Style/ Type: Lever

Material

- Premium metal construction for durability and reliability
- KOHLER finishes resist corrosion and tarnishing

Warranty

See website for detailed warranty information.

KOHLER® Faucet Lifetime Limited Warranty




1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

6-22-2026 1:17 - US-CA



Installation

- Single-hole or three-hole installation (escutcheon plate included)
- Flexible supply lines simplify installation

Installation Notes

Install this product according to the installation instructions.

ADA compliant for faucet handles only
 ADA, CSA B651 compliant when installed to the specific requirements of these regulations.

