



Claude™ by Studio McGee | K-35959

Elongated toilet bowl with skirted trapway

Features

- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 2-1/8" (54 mm) glazed trapway
- Revolution 360® flushing technology generates a forceful swirling motion to keep the bowl clean longer
- Fully skirted trapway simplifies cleaning
- Patented ReadyLock™ installation system, a simple solution for skirted toilets, saves time, hassle, and eliminates the need to drill into the floor for standard 12" (305 mm) rough-in
- CleanCoat™ surface treatment inhibits the growth of water scale and mineral stains for improved ease of cleaning
- Coordinates with other products in the Claude by Studio McGee collection
- Combines with the K-35956, K-35956-RA, K-39676, or K-39676-RA tank to create a complete K-35960, K-35960-RA, K-39678, or K-39678-RA toilet



Sustainability



Available Colors/Finishes

Color tiles intended for reference only.

- | | |
|----|-------|
| 0 | White |
| NY | Dune |

Codes/Standards

Accessibility standards may require controls to be located on the open side of the toilet.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

ASME A112.19.2/CSA B45.1

Technical Information

Rough-in:	Standard 12" (305mm)
Flush Type:	AquaPiston, Revolution 360
Flush Rate:	1.28 gpf (4.8 lpf)
Bowl Shape:	Elongated
Waste Outlet:	Floor
Trapway Size:	2-1/8" (54 mm)
Trapway Type:	Skirted
Water Surface Size:	8" x 8" (203 mm x 203 mm)
Rim to Water Surface:	7-1/16" (179 mm)

Recommended Products/Accessories

- K-35956 Toilet tank, 1.28 gpf
- K-20454 Quiet-Close™ elongated toilet seat
- K-36330-L Trip lever
- K-5383 10" rough-in full skirt trap and attachment system
- K-5381 14" rough-in full skirt trap and attachment system

Warranty

See website for detailed warranty information.

KOHLER® Toilets and Seats Limited Warranty

No image available.

This product is a component and not intended to be a standalone installation.

Installation

- Standard 12" (305 mm) rough-in
 - 10" and 14" (254 mm and 356 mm) rough-in kits also available
-

Installation Notes

Install this product according to the installation instructions.