KOHLER_®

Features

- One-piece toilets integrate the tank and bowl into a seamless, easy-to-clean design
- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 1.28 gpf (4.8 lpf)
- 2-1/8" (54 mm) fully glazed trapway
- Left-hand Polished Chrome trip lever
- AquaPiston® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush
- Easy-to-flush canister design requires less force to actuate than a 3" (76 mm) flapper, and has 90% less exposed seal material which resists conditions that cause wear, tear, shrinkage and swelling
- Cachet[®] Quiet-Close[™] seat closes quietly and quickly unlatches from the toilet for easy removal and convenient cleaning

Material

Vitreous china

Installation

- Standard 12" (305 mm) rough-in
- Supply line sold separately

Recommended Products/Accessories

K-8298 PureWash® E590 Elongated bidet toilet seat K-5420 Low-Profile Bolt Caps K-9466-L Left-Hand Trip Lever 1023457 Wax Ring/Hardware Kit 1265114 Connector Hose K-23726 Drain treatment

Included Components

K-4636 Cachet® Quiet-Close™ elongated toilet seat





ADA CSA B651 OBC

Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC) ADA ICC/ANSI A117.1 CSA B651 OBC

KOHLER[®] Toilets and Seats Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description

0	White
96	Biscuit
NY	Dune
95	lce™ Grey
-	


7 Black Black[™]







Adair® One-piece elongated toilet, 1.28 gpf K-3946



Technical Information

All product dimensions are nominal.		
Toilet type:	Floor-mount	
Waste Outlet:	Floor	
Bowl shape:	Elongated	
Flush type:	AquaPiston	
Trap passageway:	2-1/8" (54 mm)	
Water surface size:	11" x 7-3/4" (279 mm x 197 mm)	
Rim to water	6-1/16" (154 mm)	
surface:		
Rough-in:	12" (305 mm)	
Seat-mounting holes:	5-1/2" (140 mm)	

Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

