Whitehaven®



Smart Divide® 35-1/2" undermount double-bowl farmhouse kitchen sink with short apron **K-6426**

Features

- 36" minimum base cabinet width
- Large/medium bowls
- 9" (229 mm) depth provides generous workspace
- Shortened apron allows sink to be used in most standard cabinetry or retrofitted to existing standard cabinetry
- Self-Trimming® apron overlaps cabinet face for easy installation and beautiful results
- Smart Divide® feature offers a lower bowl divider that increases workspace versatility
- Bowl slopes toward drain to minimize water pooling
- Offset drain increases workspace in the sink and storage space underneath

Material

KOHLER® enameled cast iron

Installation

Undermount

Recommended Products/Accessories

K-5828 Sink Rack

K-5874 Sink Rack

K-8801 Sink drain and strainer with tailpiece

K-8799 Sink drain and strainer basket

K-23726 Drain treatment

K-23725 Cast iron cleaner

Optional Products/Accessories

K-11352 Disposal Flange with Stopper K-9000 P-Trap



Codes/Standards

ASME A112.19.1/CSA B45.2

KOHLER® Enameled Cast Iron Kitchen and Bathroom Sink Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	FF	Sea Salt™
	96	Biscuit
	NY	Dune
	95	Ice™ Grey
	58	Thunder™ Grey
	7	Black Black™
	TRF	Truffle
	17	Teal
	34	Fresh Green
	42	Aspen Green









Smart Divide® 35-1/2" undermount double-bowl farmhouse kitchen sink with short apron **K-6426**







Technical Information

All product dimensions are nominal.

Basin configuration: Large Bowl on Left Min. base cabinet 36" (914 mm)

width:

Bowl area (Basin Length: 18-13/16" (478 mm) #1): Width: 18-1/16" (459 mm)

Bowl depth: 9" (229 mm) Water depth: 4-1/2" (114 mm)

Bowl area (Basin Length: 10-5/16" (262 mm)

#2): Width: 18-1/16" (459 mm)

Bowl depth: 9" (229 mm) Water depth: 4-1/2" (114 mm)

Drain hole: 3-5/8" (92 mm)

Notes

Install this product according to the installation instructions.

NOTICE: The countertop manufacturer or cutter must use the cut-out template provided with the product, or a current one provided by Kohler Co. (call 1-800-4KOHLER). Kohler Co. is not responsible for cut-out errors when the incorrect cut-out template is used.

IMPORTANT! The distance from the top edge of the cabinet to the top of the cabinet door must be at least 6-7/8" (175 mm) to install this

sink.

