



Geberit Duofix element for wall-hung WC, 120 cm, with Alpha concealed cistern 8 cm, for wood frame wall



APPLICATION PURPOSES

- For metal and wood frame walls
- For installation in part- or room-height prewalls
- For installation in room-height partition walls
- For floor constructions 0–20 cm
- For wall-hung WCs

CHARACTERISTICS

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating
- Frame for wall-hung WCs with connection dimensions as per EN 33 and projection up to 62 cm
- Alternative fastening point for wall anchors
- Frame with \varnothing 9 mm drilling holes for fastening in wood frame construction
- Frame fulfils standard requirements in accordance with ASME A112.6.2, ANSI Z124.4
- Foot plates made of plastic
- Foot plate depth suitable for installation in U-profiles UW 50

- Galvanised leg supports protected against corrosion
- Connection bend can be mounted without tools
- Interrupted crossbar enables a front flush depth for the vertical outlet bend
- Geberit Alpha concealed cistern 8 cm fully insulated against condensation
- For front actuation, suitable for dual flush
- Immediate post flush possible with factory setting
- Cistern fulfils standard requirements in accordance with ASME A112.6.2 and ANSI Z124.4
- Flush valve fulfils standard requirements in accordance with CSA B125.3, ASME A112.19.5, IAPMO PS-50, ASME A112.19.2 in connection with ceramic appliance listed
- Fill valve fulfils standard requirements in accordance with ASSE 1002, CSA B125.3
- Water supply connection on the top left
- Protection box for service opening, can be cut to length, protects against moisture and dirt

TECHNICAL DATA

Flow pressure 10–1000 kPa

| | |
|-------------------------------|-----------|
| Water temperature max. | 25 °C |
| Flush volume, factory setting | 4.8 / 3 l |
| Product material | Steel |
| Height-adjustable | Yes |

SCOPE OF DELIVERY

- Water supply connection R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Connection set for WC, \varnothing 90 mm
- Connection bend made of PE-HD, \varnothing 90 mm
- Fastening and protection material

ACCESSORIES

- Geberit sound insulation set for wall-hung WC
- Geberit Duofix fastening material for stud clearance 50–57.5 cm
- Geberit Duofix set of wall anchor extensions
- Geberit Duofix set of foot fastener on rear wall
- Set of wall anchors for single installation, for Geberit Duofix element for wall-hung WC, with concealed cistern 8 cm

| <i>Art. no.</i> | <i>B</i> <i>cm</i> | <i>H</i> <i>cm</i> | <i>T</i> <i>cm</i> |
|----------------------------|-----------------------|-----------------------|-----------------------|
| 458.182.00.2 New | 50 | 120 | 8 |

New article available from 01.06.2026