DuraSystem # WD1022000090

Design by Duravit

In-Wall Tank & Carrier



Basic information	
Long description	Duravit DuraSystem In-Wall Tank & Carrier Standard – WD1022000090
Additional name	Standard
Article No.	WD1022000090

Classification	
Product hierarchy	
Product Type	In-Wall Tank & Carrier
Installation	
Installation Type	Drywall
Water connection type	
Dimensions of water supply connection	1/2" NPT
Water supply connection type	Male thread
Handle	
Surface treatment frame	Powder-coated
Operation	
Trip lever placement	Front
Trip lever type	Mechanical
Flush operation technology	Manual
Max. projection toilet	24 5/8 "
Water connection position	Top

Features	
Flushing	
Large flushing volume	1.6 GPF
Small flushing volume	0.8 GPF
Flush type	Dual Flush
Tank volume	1.59 gal
Minimum flushing water volume	0.8 GPF
Max. flushing water quantity	1.6 GPF

Specifications	
Self-supporting	✓
Adjustable height	9 1/2 "
Insulated tank	✓
SensoWash preparation	✓

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

DuraSystem # WD1022000090

Design by Duravit

In-Wall Tank & Carrier

Features	
Includes mounting set for wall-mounted toilet M12	✓
Includes corner valve	✓
Includes PE toilet wall-mounted outlet bend DN 90/90	✓
Includes PE toilet wall-mounted reduction DN 90/110 for outlet bend	✓
Includes tank	✓
Technical documentation	
Includes installation instructions	digital and print
Includes operating Instructions	None
Includes care instructions	None

Logistics	
Article weight	39.683 lb

Matching products
Matching items
You can find matching items on our website.

Description texts	
Tender text	Duravit DuraSystem In-Wall Tank & Carrier Standard – WD1022000090, Additional name: Standard, Max. projection toilet: 24 5/8 ", Water connection position: Top, Trip lever placement: Front, Trip lever type: Mechanical, Flush operation technology: Manual, Large flushing volume: 1.6 GPF, Small flushing volume: 0.8 GPF, Flush type: Dual Flush, Tank volume: 1.59 gal, Minimum flushing water volume: 0.8 GPF, Max. flushing water quantity: 1.6 GPF, Installation Type: In lightweight stand construction, Installation Type: Drywall, Dimensions of water supply connection: 1/2" NPT, Water supply connection type: Male thread, Surface treatment frame: Powder-coated, Adjustable height: 9 1/2 ", Insulated tank, Self-supporting, SensoWash preparation, Includes mounting set for wall-mounted toilet M12, Includes corner valve, Includes PE toilet wall-mounted outlet bend DN 90/90, Includes PE toilet wall-mounted reduction DN 90/110 for outlet bend, Includes tank, Includes installation instructions: digital and print, EAN No.: 4063382158413, Article weight: 39.683 lb, Article No.: WD1022000090

You can find more information here

https://pro.duravit.us/p/WD1022000090

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.