TOTO®

MW6444726CEFG

Carolina® II WASHLET®+ S7 One-Piece Toilet - 1.28 GPF

FEATURES

- Concealed supply connection for seamless installation
- High-efficiency TORNADO FLUSH® system - 1.28 GPF (4.8 LPF)
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Decorative one-piece with skirted design
- Universal Height
- Chrome plated trip lever
- 12" Rough-in
- Elongated front bowl and WASHLET+ S7 and tank set
- EWATER+® auto-cleans wand and bowl after every use
- PREMIST® automatically mists the bowl before each use
- Multifunction pearl white block-style remote control
- Night light

MODELS

- **MW6444726CEFG (#01)**
  With CEFIONTECT ceramic glaze, WASHLET+ S7 with contemporary design
  - **CST644CEFGAT40**
    Elongated bowl with CEFIONTECT
  - **SW4726AT40**
    WASHLET+ S7

OPTIONAL COMPONENTS

- **TSU01W.10R**
  10" Unifit Rough-In
- **TSU01W.14R**
  14" Unifit Rough-In
- **THU808(#01, #03, #11, #12, #51, #BN, #PN, #RB)-A**
  Trip Lever (Cotton, Bone, Colonial White, Sedona Beige, Ebony, Brushed Nickel, Polished Nickel, Oil Rubbed Bronze)

COLORS/FINISHES

- #01 Cotton

TORNADO FLUSH   **UNIVERSAL HEIGHT**

CEFIONTECT   **EWATER+**

PRODUCT SPECIFICATION

The one-piece high-efficiency TORNADO FLUSH system toilet shall be 1.28 GPF (4.8 LPF). Toilet shall be 12" Unifit rough-in. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl with SoftClose seat and Polished Chrome trip lever.
Toilet shall be TOTO Model MW6444726CEFG___#01.

See SW4726AT40 Specification Sheet for details on included WASHLET.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO (cUPC®), EPA WaterSense®, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant for residential use when installed with trip lever located on the approach side
- Complies with CA Prop 65 warning requirements

SPECIFICATIONS

Water Use	1.28 GPF (4.8 LPF)
Flush System	TORNADO FLUSH®
Min. Water Pressure	8 psi (Flowing)
Water Surface	6-5/8" x 9-1/8"
Trap Diameter	2-1/8"
Rough-in	12" (10" and 14" options available)
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	CST644CEFGT40: 110 lbs SW4726AT40: 14.5 lbs
Shipping Dimensions	CST644CEFGT40 29-1/2" L x 18-1/4" W x 25-1/2" H SW4726AT40 23-3/8" L x 17-5/8" W x 6-1/4" H

*See SW4726AT40 Specification Sheet for details on included WASHLET.*

INSTALLATION NOTES

Back-to-Back Toilet Installations:
TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.

Double Combination Wye / 1/8 Bend	Double Sanitary Tee / Sanitary Cross
YES	**NO**

To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS

**GFCI outlet of 120V, 15A
Washlet power cord is 4' long with 3 prongs.